

LED Lighting Units | LED Leuchte

Airtight Single, Airtight Twin

500071,500072,500073,500074,500075,500076,500077 - 01/2018

Phaesun Airtight Lighting Units are especially designed for outdoor use.

Due to the highly efficient LED tubes they provide immediate bright lighting without cold-start problems. Airtight is often combined with motion detectors. The lighting units are available in different versions.

Diese Leuchten garantieren sofort helle und effiziente Beleuchtung und eignen sich somit perfekt für Terrassen oder den Gebrauch in Kombination mit Bewegungsmeldern. Perfekt für den Gebrauch im Freien Dank IP65!



Airtight Single



Airtight Twin

Technical Data	Technische Daten	Airtight Single 1000_12-60	Airtight Twin 2000_12-60	Airtight Single 2000_12-120	Airtight Twin 4000_12-120	Airtight Single 1000_24-60	Airtight Twin 2000_24-60	Airtight Single 2000_24-120	Airtight Twin 4000_24-120
System voltage	V	12	12	12	12	24	24	24	24
Voltage range	VDC	11...20	11...20	11...20	11...20	22...30	22...30	22...30	22...30
Tube size	Röhren Abmessung	1x54	2x54	2x54	4x54	1x54	2x54	2x54	4x54
Current	A	0,8	1,7	1,7	3,4	0,4	0,8	0,8	1,7
Power	W	10	20	20	40	10	20	20	40
Light temperature	Licht Temperatur	K	5700	5700	5700	5700	5700	5700	5700
Lumen	lm	1000	2000	2000	4000	1000	2000	2000	4000
Efficiency	Wirkungsgrad	lm/W	100	100	100	100	100	100	100
Ambient temperature	Umgebungs- temperatur		-20 ... 50 °C	-20 ... 50 °C	-20 ... 50 °C	-20 ... 50 °C	-20 ... 50 °C	-20 ... 50 °C	-20 ... 50 °C
Protective function	Schutzfunktion		Wrong polarity, over temperature Verpölung, Übertemperatur	Wrong polarity, over temperature Verpölung, Übertemperatur	Wrong polarity, over temperature Verpölung, Übertemperatur	Wrong polarity, over temperature Verpölung, Übertemperatur	Wrong polarity, over temperature Verpölung, Übertemperatur	Wrong polarity, over temperature Verpölung, Übertemperatur	Wrong polarity, over temperature Verpölung, Übertemperatur
Lifetime	Lebensdauer	h	36000	36000	36000	36000	36000	36000	36000
Beam Angle	Abstrahlwinkel		180°	180°	180°	180°	180°	180°	180°
Ingress Protection	IP-Schutz		IP65	IP65	IP65	IP65	IP65	IP65	IP65
Dimension	Abmessung	mm	680x90x100	1280x90x100	1280x150x100	680x90x100	680x150x100	1280x90x100	1280x150x100
Weight	Gewicht	kg	0,7	1,4	2,0	0,7	1,0	1,4	2,0
Art.-No.	Art.-Nr.	500071	500072	500075	500078	500073	500074	500076	500077